# SPIROL

# **COMPRESSION LIMITERS**

# **SPIROL®** CL220 Split Seam Compression Limiters

The Series CL220 Split Seam Compression Limiter is installed into a hole after the moulding process. The spring force generated during installation provides self-retention in the assembly. The flexible diameter accommodates wide hole tolerances, and the gap is designed such that the parts will not interlock in the free state. Once installed, the CL220 provides a minimum clearance of 1mm over the bolt diameter to compensate for misalignment. The CL220 is the only standard Compression Limiter finished with a protective coating of ArmorGalv®. Rated for use up to ISO Class 8.8 bolts, the CL220 Compression Limiter offers the widest range of standard diameter and length combinations to accommodate a variety of application requirements.




#### What is ArmorGalv®?

ArmorGalv® is a zinc alloy thermal diffusion coating covered by ASTM A1059M-08(2013) that provides uniform deposition of coating on all surfaces of the part. There are no insignificant surfaces and the entire inner diameter receives full coating and protection. ArmorGalv® offers a minimum of **1,000+ hours corrosion resistance** to red rust, and is an ideal coating for some of the most aggressive environments such as marine, automotive, agricultural, mining and industrial manufacturing. Additional benefits include:

- · ZERO risk of hydrogen embrittlement
- · Will not reduce fatigue strength of material
- · Uniform deposition of coating on all surfaces
- Anti-galling characteristics similar to cadmium
- · No flaking, peeling, or blistering
- · Hard and highly abrasion resistant @ 37-42 HRC
- Slightly porous surface will retain paint and other coatings



SPIROL is a licensee of ArmorGalv®, a registered trademark of Distek N.A LLC




#### **Application Engineering Support**

Partner with SPIROL's Application Engineers early in the design stage to help you select the most appropriate Compression Limiter to ensure bolted joint integrity throughout the life of the assembly.

Contact SPIROL for design assistance: www.SPIROL.co.uk

# **CL220 Split Seam Compression Limiter Specifications**





MATERIAL

B High Carbon Steel

FINISH
H ArmorGalv®

#### **DIMENSIONAL DATA**

NOMINAL BOLT SIZE ►		M4	M5	M6	M8	M10	M12
Min. ØID Installed		5.0	6.0	7.0	9.0	11.0	13.0
Wall Thickness "T"		0.85	1.00	1.10	1.50	1.85	2.25
Length Tolerance "L <sub>Tol</sub> "		0.15	0.15	0.15	0.20	0.25	0.25
Outer Diameter ØOD		7.17/7.34	8.47/8.64	9.67/9.89	12.52/12.79	15.27/15.59	18.07/18.44
Recommended Ø Hole Size		7.00/7.10	8.30/8.40	9.50/9.60	12.35/12.45	15.10/15.20	17.90/18.00
LENGTH	6						
	8						
	10						
	12						
	15						
	20						
	25		_				
	30						

- CL220 rated for use up to ISO Class 8.8.
- · Special lengths and sizes available upon request.

To Order: CMPL, Nominal Bolt Size, Length, Material, Finish, Series

Example: CMPL 6 X 8 BH CL220

# **Installation Technology for Compression Limiters**

SPIROL offers robust, vertical installation machines specifically designed to post-mould install Compression Limiters into a variety of plastic assemblies. The machines can install a single Compression Limiter or multiple Compression Limiters simultaneously into various polymers, thermoplastics and thermosets.

#### **Standard Models include:**

- Model CM Manual Compression Limiter Installation Machine
- Model CL Semi-Automatic Compression Limiter Installation Machine
- Model CLX Extra-Large Semi-Automatic Compression Limiter Installation Machine

Each one of SPIROL's standard Compression Limiter Installation Machines can be customised to meet your specific application and assembly requirements.





Check out SPIROL's entire Installation Technology offering on SPIROL.co.uk!



# PIROL Innovative fastening solutions. Lower assembly costs.











**Tubular Components** 



Compression Limiters

**Alignment Dowels / Bushings** 







Threaded Inserts for Plastics


**Railroad Nuts** 

**Disc Springs** 



**Precision Shims &** 

**Thin Metal Stampings** 





**Parts Feeding Technology** 





**Insert Installation Technology** 



**Compression Limiter Installation Technology** 

Please refer to www.SPIROL.co.uk for current specifications and standard product offerings.

SPIROL offers complimentary Application Engineering support! We will assist on new designs as well as help resolve issues, and recommend cost savings on existing designs. Let us help by visiting Application Engineering Services on SPIROL.co.uk.

#### **Technical Centres**

**Europe SPIROL United Kingdom** 17 Princewood Road Corby, Northants NN17 4ET United Kingdom Tel: +44 (0) 1536 444800 Fax: +44 (0) 1536 203415

#### **SPIROL France**

Cité de l'Automobile ZAC Croix Blandin 18 Rue Léna Bernstein 51100 Reims, France Tel: +33 (0) 3 26 36 31 42 Fax: +33 (0) 3 26 09 19 76

#### **SPIROL Germany**

Ottostr. 4 80333 Munich, Germany Tel: +49 (0) 89 4 111 905 71 Fax: +49 (0) 89 4 111 905 72

#### SPIROL Spain

Plantes 3 i 4 Gran Via de Carles III, 84 08028, Barcelona, Spain Tel/Fax: +34 932 71 64 28

#### SPIROL Czech Republic

Evropská 2588 / 33a 160 00 Prague 6-Dejvice Czech Republic Tel: +420 226 218 935

#### **SPIROL Poland**

ul. Solec 38 lok. 10 00-394, Warsaw, Poland Tel. +48 510 039 345

#### **Americas**

#### **SPIROL International Corporation**

30 Rock Avenue Danielson, Connecticut 06239 U.S.A. Tel. +1 860 774 8571 Fax. +1 860 774 2048

#### **SPIROL Shim Division**

321 Remington Road Stow, Ohio 44224 U.S.A. Tel. +1 330 920 3655 Fax. +1 330 920 3659

#### SPIROL Canada

3103 St. Etienne Boulevard Windsor, Ontario N8W 5B1 Canada Tel. +1 519 974 3334 Fax. +1 519 974 6550

#### **SPIROL Mexico**

Avenida Avante #250 Parque Industrial Avante Apodaca Apodaca, N.L. 66607 Mexico Tel. +52 81 8385 4390 Fax. +52 81 8385 4391

#### **SPIROL Brazil**

Rua Mafalda Barnabé Soliane, 134 Comercial Vitória Martini, Distrito Industrial. CEP 13347-610, Indaiatuba, SP, Brazil Tel. +55 19 3936 2701 Fax. +55 19 3936 7121

### **Pacific**

**SPIROL** Asia Headquarters

1st Floor, Building 22, Plot D9, District D No. 122 HeDan Road Wai Gao Qiao Free Trade Zone Shanghai, China 200131 Tel: +86 (0) 21 5046-1451 Fax: +86 (0) 21 5046-1540

#### SPIROL Korea

16th Floor, 396 Seocho-daero, Seocho-gu, Seoul, 06619, South Korea Tel: +82 (0) 10 9429 1451

e-mail: info-uk@spirol.com